

Tilgængelige bukkeradier: overkniv & sporbrede			
4 mtr	R1 - 30°	V 8	30°
4 mtr	R1.2 Høj	V 10	30°
4 mtr	R1.5 - 85°	V 16	30°
4 mtr	R3 - 85°	V 20	30°
4 mtr	R5 - 30°	V 24	30°
4 mtr	R10 - 30°	V 32	30°
4 mtr	R15 - 60°	V 40	60°
4 mtr	R20 - 60°	V 50	60°
4 mtr	R25 - 60°	Rv 64	60°
4 mtr	R30 - 60°	Rv 80	60°
4 mtr	R40 - 60°	Rv 100	60°
4 mtr		Rv 120	60°
4 mtr		Rv160	80°

R = Radius

S = Spor

Rv = Rulleværktøj

S355 - 90°

Tykkelse	R min	Spor normal	L Maks	Spor min	L Maks	Antal anslag i mm	Tons
1 mm	R 1	S 8	4 mtr	S 8	4 mtr	4,5	44,9
2 mm	R 3	S 16	4 mtr	S 16	4 mtr	9	89,7
3 mm	R 3	S 24	4 mtr	S 20	4mtr	13,5	134,6
4 mm	R 5	S 32	4 mtr	S 24	4mtr	18	179,7
5 mm	R 5	S 40	4 mtr	S 32	4 mtr	22,5	280
6 mm	R 10	S 50	4 mtr	S 40	4 mtr	28	323
8 mm	R 10	Rv 64	3,5 mtr	S 50	2,8 mtr	36	325
10 mm	R 10	Rv 80	2,9 mtr	Rv64	2,3 mtr	45	322
12 mm	R 15	Rv 100	2,5 mtr	Rv80	2 mtr	56	325,1
15 mm	R 15	Rv 120	1,9 mtr	Rv100	1,2 mtr	67,5	323
20 mm	R 20	Rv 160	1,45 mtr			90	329,1

Anvendelse af STEP-filer: Ja